

# SM150RS/W

## Aluminum Front IP65 5 wire Resistive Touch Monitor



### Feature

- ✓ Fanless design and compact solution
- ✓ IP65 compliant thickness aluminum front bezel
- ✓ Resolution: 1024 x 768 dpi
- ✓ 5 wires resistive touch solution
- ✓ Silver anodic aluminum front bezel
- ✓ Rich I/O ports for choice.
- ✓ Panel mount & VESA mounting & Clips

I/O Port			
SM150RS/W03	SM150RS/W04	SM150RS/W05	SM150RS/W06
VGA	VGA	VGA	DP
DVI	HDMI	HDMI	DVI
/	DP	DVI	/
USB or RS232	USB or RS232	USB or RS232	USB or RS232
Power			
DC IN 12 V			
Touch Screen		OS Support	
5 wire resistive		Win 7.8.10; Win Embedded 7,8,10, Win pro 7,8,10	
Display			
Size		15" TFT (4:3)	
Resolution		1024 x 768	
Colors		16.2 M	
Luminance ( cd/m2)		400	
Contrast Ratio		700:1	
View Angle ( H / V )		160/160	
Mechanical & Environmental			
Operation Temperature		0 ~ 45°C for SM-150RS ; -20~55°C for SM-150RW	
Storage Temperature		-10°C ~ 70°C	
Storage Humidity		10 ~ 90%, non-condensing	
Mount		Clip mount, Panel mount & VESA mounting(100X100mm)	
Dimension (W x H x D mm)&Weight		303.7 x 400.9 x 71 (9.5kg)	
Optional			
Clip		10	
Rack Mount Bezel		1	
Magnetic Bezel		1	
Optical Bonding		1	
No Touch Screen		1	
AR Glass		1	

Optional High Brightness Panel					
Resolution	1024 x 768				
Color	16.2 M	16.7 M	16.7 M	16.2 M	16.7 M
Luminance(cd/m2)	2000	1600	1000	1000	800
Contrast Ratio	700:1	700:1	1700:1	700:1	700:1
Viewing Angle (H/V°)	160/160	160/160	170/170	160/160	160/160

\*\* Specifications are subject to change without notice.

Inspiring a Reliable Solution  
www.kingdy.com.tw

